

## County Surveyor's Record, Douglas County, Oregon

Tract 37, Section 13, T. 28 S., R. 4 W.

CHAINS

from which

A fir, 7 ins. diam., bears N.  $40\frac{3}{4}^{\circ}$  E., 119.5 lks. dist., marked AP S13 BT.

Set a steel fence post, 6 ft. long, alongside the iron post.

From this same point, the N.E. corner of a wood frame house bears S.  $46^{\circ} 21'$  W., 1.71 chs. dist., dimensions  $36\frac{1}{2} \times 24$  ft., long side bears E. and W.

N.  $88^{\circ} 00'$  W., on line 1-2 of Tract No. 37.

Descend 2 ft. over bottom land.

1.75 Point for angle point No. 2 of Tract No. 37.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam, 22 ins. in the ground, with brass cap mkd.

T 28 S R 4 W  
 S 13  
 AP 2  
 TR 37  
 1965

from which

A fir, 8 ins. diam., bears N.  $31^{\circ}$  W.,  $122\frac{1}{2}$  lks. dist., marked AP S13 BT.

Set a steel fence post 6 ft. long, alongside the iron post.

---

Thence S.  $69^{\circ} 00'$  W., on line 2-3 of Tract No. 37.

Descend 1 ft. over bottom land.

0.85 Point for angle point No. 3 of Tract No. 37.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T 28 S R 4 W  
 S 13  
 AP 3  
 TR 37  
 1965

Set a steel fence post, 6 ft. long, alongside the iron post.

There is no suitable bearing tree within limits.

---

Thence S.  $52^{\circ} 00'$  W., on line 3-4 of Tract No. 37.

Descend 2 ft. over bottom land.