

County Surveyor's Record, Douglas County, Oregon

Tract 37, Section 13, T. 28 S., R. 4 W.

CHAINS

3.30

Point for angle point No. 4 of Tract No. 37.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 4 W
S 13
AP 4
TR 37
1965

from which

A fir, 10 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ W., 195 $\frac{1}{2}$ lks. dist., marked AP S13 BT.

Set a steel fence post, 6 ft. long, alongside the iron post.

 Thence S. $33^{\circ} 00'$ E., on line 4-5 of Tract No. 37.

Descend 6 ft. over bottom land.

2.05

Point for angle point No. 5 of Tract No. 37, on the N. bank of Buck Fork of North Myrtle Creek, 10 lks. wide, course N. 80° W.Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

AP 5
TR 37
S 13
T 28 S R 4 W
1965

from which

A cedar, 31 ins. diam., bears S. $54\frac{1}{2}^{\circ}$ E., 117 lks. dist., marked AP S13 BT.

Set a steel fence post, 6 ft. long, alongside the iron post.

 Thence N. $56^{\circ} 00'$ E., on line 5-6 of Tract No. 37.

Ascend 6 ft. along the N. bank of creek.

2.60

Point for angle point No. 6 of Tract No. 37, on N. bank of Buck Fork of North Myrtle Creek.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

AP 6
TR 37
S 13
T 28 S R 4 W
1965

from which

A cedar, 10 ins. diam., bears S. $31\frac{3}{4}^{\circ}$ E., 99 lks. dist., marked AP S13 BT.