

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS

- A burned fir stump, 18 ins. diam., bears N. 28° E.,
38 lks. dist., with no marks remaining.
- A burned fir stump, 42 ins. diam., bears S. 24° W.,
40 lks. dist., with no marks remaining.
- A burned and down fir, 36 ins. diam., bears N. 45° W.,
92 lks. dist., with no marks remaining.

and bearing trees marked by Haines

- A dead fir, 10 ins. diam., bears N. 30° E., 53 lks.
dist., with scribe marks T22S R7W S23 BT visible
on unhealed blaze.
- A dead white fir, 5 ins. diam., bears S. 69° E.,
42½ lks. dist., with scribe marks T22S R7W S26
BT visible on unhealed blaze.

and bearing trees marked by James W. Byron, Deputy County
Surveyor, in 1960

- A fir, 9 ins. diam., bears N. 19° E., 152 lks.
dist., with double healed blaze.
- A sawed fir stump, 52 ins. diam., bears S. 34° W.,
61 lks. dist., with scribe marks T22S R7W S27 CS
BT visible on unhealed blaze.
- A broken fir stump, 18 ins. diam., bears N. 9° W.,
168 lks. dist., with no marks remaining.

at the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 22 S R 7 W
S 22 | S 23
S 27 | S 26
1965

from which new bearing trees

- A cedar, 10 ins. diam., bears S. 41½° W., 78 lks.
dist., mkd. T22S R7W S27 BT.
- A fir, 10 ins. diam., bears N. 26° W., 157 lks.
dist., mkd. T22S R7W S22 BT.

Deposit local T iron and iron rod alongside the
iron post.N. 0° 27' E., bet. secs. 22 and 23, marking and blazing
the true line.Descend 140 ft. over NW. slope, through heavy timber and
dense undergrowth.

- 6.55 Creek, 1 lk. side, course S. 80° W.; asc. 240 ft. over
broken S.W. slope.
- 7.95 Gravelled road, 20 lks. wide, bears N. 75° E. and S. 75° W.
- 22.50 Leave timber; enter clear cut logged area, edge bears
generally E. and W.
- 30.00 Spur, slopes N. 75° W.; desc. 115 ft. over N. slope.