

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS

bet. secs. 15 and 22, because no correlation was ever established bet. the original  $\frac{1}{4}$  sec. cor. or the witness point and the cor. of secs. 14, 15, 22 and 23.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 7 W
S 15   S 14
S 22   S 23
1965

from which

A white fir, 25 ins. diam., bears N.  $22\frac{1}{2}^{\circ}$  E., 399 lks. dist., mkd. T22S R7W S14 BT.

A fir, 12 ins. diam., bears S.  $83\frac{3}{4}^{\circ}$  E., 283 lks. dist., mkd. T22S R7W S23 BT.

A fir, 11 ins. diam., bears S.  $81\frac{1}{4}^{\circ}$  W., 383 lks. dist., mkd. T22S R7W S22 BT.

A white oak, 12 ins. diam., bears N.  $74^{\circ}$  W., 221 lks. dist., mkd. T22S R7W S15 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, madrone, dogwood, alder, ash, yew and chinquapin; undergrowth, vine maple, salal, ocean spray, Oregon grape, hazel, huckleberry, blackberry, salmonberry, poison oak, and fern.

From the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23, perpetuated and recorded by Wilford N. Haines, REgistered Land Surveyor, in 1958, monumented with a 1 in. T iron, firmly set, extending 12 ins. above the ground, with brass disc marked, Wilford N. Haines, 239 Survey Point, Drain, Oregon, from which the original bearing trees:

A fir, 64 ins. diam., bears N.  $31^{\circ}$  E., 83 lks. dist., no original scar evident, has been remarked, scribe marks  $\frac{1}{4}$  S14 363 BT visible on bark blaze.

The stump hole of a fir, bears S.  $40^{\circ}$  W., 48 lks. dist.

And a bearing tree marked by S. W. Cole, Deputy County Surveyor in 1913.

A black oak, 20 ins. diam., bears S.  $41\frac{3}{4}^{\circ}$  E., 150 lks. dist., with opened double blaze, no marks remaining.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 22 S R 7 W
$\frac{1}{4}$ S 14
S 23
1965

from which a new bearing tree

A fir, 4 ins. diam., bears S.  $43^{\circ}$  E., 8 lks. dist., mkd. X BT.

Deposit T iron alongside the iron post.