

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W ¼ S 11 S 14 1965</p> <p>from which new bearing trees</p> <p>A fir, 23 ins. diam., bears N. 10° E., 64 lks. dist. mkd. ¼ S11 BT.</p> <p>A fir, 11 ins. diam., bears S. 3¼° W., 63½ lks. dist., mkd. ¼ S14 BT.</p> <p>Deposit T iron alongside the iron post.</p> <p>S. 88° 01' W., bet. secs. 11 and 14.</p> <p>Descend 385 ft. over W. slope, across logged area, through scattering timber and dense undergrowth.</p> <p>26.50 Gravelled road, 30 lks. wide, bears N. 10° E. and S. 10° W.</p> <p>29.00 Elk Creek, 75 lks. wide, course N.; asc. 75 ft. over SE. slope.</p> <p>39.23 The cor. of secs. 10, 11, 14, and 15.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, maple, madrone, dogwood, alder ash, yew, and chinquapin; Undergrowth, vine maple, salal, ocean spray, Oregon grape, hazel, huckleberry, blackberry, salmonberry, poison oak, and fern.</p>
	<p>N. 1° 29' W., bet. secs. 10 and 11.</p> <p>Ascend 375 ft. over SE. slope, across logged area, through scattering timber and dense undergrowth.</p> <p>22.00 Ridge, bears N. 20° E. and S. 20° W.; asc. 25 ft. along W. slope.</p> <p>27.30 Top of ascent, slopes W.; desc. 140 ft. over NW. slope, changing to N. slope.</p> <p>40.33 The ¼ sec. cor. of secs. 10 and 11, reestablished at proportionate distance by Wilford N. Haines, Registered Land Surveyor, in 1960, and recorded with the Douglas County Surveyor, monumented with a 1 in. T iron, firmly set, extending 10 ins. above the ground, with brass disc marked Wilford N. Haines, 239 Survey Point, Drain, Oregon, from which bearing trees marked by Haines:</p> <p>A fir, 15 ins. diam., bears S. 12¼° E., 17 lks. dist., with partly healed blaze.</p> <p>A fir, 8 ins. diam., bears N. 52° W., 6 lks. dist., with partly healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>