

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS

T 22 S R 7 W  
 $\frac{1}{4}$   
 S 10 | S 11  
 1965

Deposit T iron alongside the iron post.

N. 1° 29' W., beginning new measurement.

Descend 325 ft. over N. slope.

8.40 Elk Creek, 100 lks. wide, course S. 60° W.; asc. 510 ft. over S. slope.

12.95 Gravelled road, 30 lks. wide, bears N. 65° E. and S. 65° W.

40.29 The cor. of secs. 2, 3, 10 and 11, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, in 1960, monumented with a 1 in. T iron, firmly set, extending 12 ins. above the ground, with brass disc marked Wilford N. Haines, 239 Survey Point, Drain Oregon, from which the remaining original bearing trees:

A fir, 67 ins. diam., bears N. 32° E., 46 lks. dist., with illegible scribe marks visible on bark blaze, and with scribe marks T22S R7W BT 363 on new bark blaze. (Record, N. 40° E.)

A stump hole, bears S. 22½° E., 40 lks. (Record, S. 28° E.)

A maple, 30 ins. diam., bears S. 56° W., 31 lks. dist., with scribe marks visible in negative on overgrowth.

and a bearing tree marked by Haines

A fir, 25 ins. diam., bears S. 11 ¾° E., 61 lks. dist., marked T22S R7W S11 BT on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to bedrock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 22 S R 7 W  
 $\frac{1}{4}$   
 S 3 | S 2  
 S 10 | S 11  
 1965

from which a new bearing tree

A fir, 35 ins. diam., bears N. 31 ¾° W., 86 lks. dist., mkd. T22S R7W S3 BT.

Deposit T iron alongside the iron post.

Land, mountainous.

Soil, rock clay loam.

Timber, fir, hemlock, cedar, maple, madrone, dogwood, alder, ash, yew, and chinquapin; undergrowth, vine maple, salal, ocean spray, Oregon grape, hazel, huckleberry, blackberry, salmonberry, poison oak, and fern.