

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

## CHAINS

From the cor. of secs. 14, 15, 22, and 23.

N.  $82^{\circ} 17'$  W., bet.s secs. 15 and 22.Descend 400 ft. over SW. slope, changing to W. slope,  
across open pasture land.1.71 Barbed wire fence, bears N. and S.; leave pasture, enter  
logged area with scattering timber and dense undergrowth.20.25 Ravine, drains N.  $55^{\circ}$  W.; desc. 85 ft. over W. slope.23.61 Elk Creek, 150 lks. wide, from N.  $30^{\circ}$  E., course S.  $60^{\circ}$  W.;  
from this point the original witness point on the right  
bank of Elk Creek, established by Gordon and Gardner, in  
1855, bears North, 2.03 chs. dist., perpetuated and  
recorded by Milo E. Godfrey, Deputy County Surveyor, in  
1962, monumented with an iron post, 1 in. diam., firmly  
set, extending 6 ins. above the ground, with brass cap  
mkd. County Surveyors Office T22S R7W WC S15 S22 1962,  
from which the remaining original bearing tree:A double cedar, 45 ins. diam., bears N.  $11\frac{1}{2}^{\circ}$  W.,  
42 lks. dist., with scribe marks S T22 R7W BT  
visible on partly healed blaze.

and bearing trees marked by Godfrey

A fir, 8 ins. diam., bears N.  $46^{\circ}$  W.,  $37\frac{1}{2}$  lks. dist.,  
with healed double blaze.A fir, 10 ins. diam., bears S.  $86^{\circ}$  W.,  $43\frac{1}{2}$  lks. dist.,  
with healed double blaze.

Ascend 190 ft. over SE. slope.

28.90 Oregon State Highway No. 38, 30 lks. wide, bears N.  $40^{\circ}$  E.,  
and S.  $40^{\circ}$  W.38.46 The original  $\frac{1}{4}$  sec. cor. of secs. 15 and 22, established  
by Gordon and Gardner, in 1855, perpetuated and recorded  
by Milo E. Godfrey, Deputy County Surveyor, in 1962,  
monumented with an iron post, 1 in. diam., firmly set,  
extending 8 ins. above the ground, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 22 S

1855

 $\frac{1}{4}$  S 15

S 22

R 7 W

1962

from which the original bearing trees

A fir snag, 78 ins. diam., bears N.  $51^{\circ}$  E., 143 lks.  
dist., with a portion of bark blaze visible, no  
scribe marks remaining.A down firm buried in swampy ground, size indeterminate,  
bears S.  $16^{\circ}$  E., 145 lks. dist.

and bearing trees marked by Godfrey

A fir, 10 ins. diam., bears N.  $28^{\circ}$  E., 30 lks. dist.,  
with healed double blaze.A fir, 14 ins. diam., bears S.  $50^{\circ}$  E.,  $25\frac{1}{2}$  lks. dist.,  
with healed double blaze.

Corner is at top of ascent, slopes S.