

County Surveyor's Record, Douglas County, Oregon

Dependnet Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS	
22.20	Wire fence, bears E. and W.; enter open pasture land, edge bears same as fence.
34.00	Ridge, bears N. 35° W. and S. 35° E.; enter logged area with scattering timber and dense undergrowth, edge bears same as ridge; desc. 120 ft. over NE. slope.
39.36	The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, determined at record bearing and distance from the remaining original bearing tree: A dead fir, 35ins. diam., bears N. 38° W., 35 lks. dist., with scribe marks $\frac{1}{4}$ S C S16 visible on bark blaze. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T 22 S R 7 W S 16 S 15 1965 from which a new bearing tree A fir, 21 ins. diam., bears N. 68° E., 55 lks. dist., mkd. $\frac{1}{4}$ S15 BT. N. 0° 24' W., beginning new measurement. Descend 150 ft. over broken NE. slope, generally along the E. edge of logged area, through scattering timber and dense undergrowth.
21.50	Ravine, drains E.; asc. 335 ft. over broken SE. slope.
39.10	The cor. of secs. 9, 10, 15, and 16, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor, in 1960, monumented with 1 in. T iron, firmly set, extending 8 ins. above the ground, with brass disc marked Wilford N. Haines, 239 Survey Point, Drain, Oregon, from which the remaining original bearing trees: A fir, 31 ins. diam., bears S. 65° E., 6 lks. dist., no marks evident. A down madrone, 15 ins. diam., bears N. 85° W., 4 lks. dist., with old axe marks. and bearing trees marked by Haines. A fir, 20 ins. diam., bears N. 32 $\frac{1}{4}$ ° E., 37 lks. dist., with scribe marks T22S R7W S10 BT 363 visible on bark blaze. A fir, 30 ins. diam., bears N. 28° W., 36 lks. dist., with scribe marks T22 R7W S9 BT 363 visible on bark blaze. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

*pd ok 5/15/89
M 108-22 CS 63/91
L. Roberts*