

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 22 S., R. 7 W.

CHAINS

$$\begin{array}{r} T\ 22\ S\ R\ 7\ W \\ \hline S\ 9\ |S\ 10 \\ S\ 16\ |S\ 15 \\ 1965 \end{array}$$

*Fd. OK 5/4/89  
L. P. Rogers  
C.S. 43/91  
M 100-22*

from which new bearing trees

An oak, 10 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  E., 85 $\frac{1}{2}$  lks.  
dist., mkd. T22S R7W S15 BT.

A fir, 21 ins. diam., bears S.  $68^{\circ}$  W., 200 lks.  
dist., mkd. T22S R7W S16 BT.

Deposit T iron alongside the iron post.

Corner is on a spur, slopes SE.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, madrone, dogwood, alder,  
yew, chinquapin, and oak; undergrowth, vine maple, salal,  
ocean spray, Oregon grape, hazel, huckleberry, blackberry,  
salmonberry, poison oak, and fern.

From the cor. of secs. 10, 11, 14 and 15.

N.  $88^{\circ} 12'$  W., bet. secs. 10 and 15.

Ascend 295 ft. over SE. slope, generally along the S. edge  
of logged area, through scattering timber and dense under-  
growth.

7.80 Ridge, bears N.  $15^{\circ}$  E. and S.  $15^{\circ}$  W.; desc. 385 ft. over  
W. slope.

18.30 Elk Creek, 75 lks. wide, course S.  $30^{\circ}$  W.; asc. 5 ft.  
over SE. slope.

19.43 Point for the E 1/16 sec. cor. of secs. 10 and 15, on  
the W. bank of Elk Creek.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, and in a mound of stone, 3 ft. base, to top,  
with brass cap mkd.

$$\begin{array}{r} E\ 1/16\ \frac{S\ 10}{S\ 15} \\ 1965 \end{array}$$

from which

An ash, 17 ins. diam., bears N.  $39\frac{1}{4}^{\circ}$  E., 241 lks.  
dist., mkd. E 1/16 S10 BT.

A cedar, 25 ins. diam., bears S.  $75\frac{1}{2}^{\circ}$  W., 99 lks.  
dist., mkd. E 1/16 S15 BT.

Ascend 105 ft. over SE. slope.

32.50 Top of ascent, slopes S.; desc. 30 ft. over SW. slope.

38.86 The  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, reestablished at  
proportionate distance by Wilford N. Haines, Registered  
Land Surveyor, in 1960, and recorded with the Douglas  
County Survey, monumented with a 1 in. T iron, firmly  
set, extending 6 ins. above the ground, with brass disc  
marked Wilford N. Haines, 239 Survey Point, Drain, Oregon  
from which bearing trees marked by Haines: