

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 22 S., R. 7 W.

CHAINS	
	<p>An oak, 12 ins. diam., bears N. 69° W., 66 lks. dist., mkd. CS 1/16 S15 BT.</p> <p>Corner is on a ridge, bears N. 70° W. and S. 60° E.; leave pasture land, enter heavy timber and dense undergrowth, edge bears same as ridge, desc. 345 ft. over N. slope.</p>
32.00	<p>Elk Creek, 150 lks. wide, course E.; asc. 110 ft. over S. slope.</p>
37.22	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 15, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 7 W C $\frac{1}{4}$ S 15 1965</p> <p>from which</p> <p>A white fir, 22 ins. diam., bears S. 70° E., 18 lks. dist., mkd. C $\frac{1}{4}$ S15 BT.</p> <p>A maple, 12 ins. diam., bears N. 63° W., 70 lks. dist., mkd. C $\frac{1}{4}$ S15 BT.</p> <p>Ascend 310 ft. over S. slope, changing to SW. slope.</p>
46.80	<p>Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.</p>
57.15	<p>Point for the center N 1/16 sec. cor. of sec. 15.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 15 C 1965</p> <p>from which</p> <p>A fir, 24 ins. diam, bears S. 79° E., $85\frac{1}{2}$ lks. dist., mkd. CN 1/16 S15 BT.</p> <p>A fir, 45 ins. diam., bears S. 55° W., 15 lks. dist., mkd. CN 1/16 S15 BT.</p> <p>Ascend 65 ft. over SW. slope.</p>
62.50	<p>Spur, slopes N. 70° W.; desc. 485 ft. over N. slope.</p>
73.00	<p>Elk Creek, 150 lks. wide, course N. 70° W.; asc. 95 ft. over S. slope.</p>
77.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p> <p>N. 87° 11' W., on the E. and W. center line of sec. 15.</p> <p>Ascend 320 ft. over NE. slope, through heavy timber and dense undergrowth.</p>