

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 15, T. 22 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

NE 1/16 S15
1965

SEE BLM 2018 RESURVEY
DCSO PGS 23748
FD BC AND 1 BT
1 NEW BT

from which

A maple, 17 ins. diam., bears S. 80° E., 21 lks. dist., mkd. NE 1/16 S15 BT.

A fir, 7 ins. diam., bears N. 12° W., 38 lks. dist., mkd. NE 1/16 S15 BT.

Ascend 40 ft. over SW. slope.

- 22.50 Spur, slopes W.; desc. 680 ft. over NW. slope.
- 38.30 Elk Creek, 150 lks. wide, course S. 60° W.; asc. 3 ft. over creek bank.
- 40.08 The E 1/16 sec. cor. of secs. 10 and 15.

From the N 1/16 sec. cor. of secs. 14 and 15.

N. $87^{\circ} 44'$ W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 15.

Ascend 630 ft. over SE. slope, changing to E. slope, through heavy timber and dense undergrowth.

- 17.70 Ridge, bears N. and S. 30° E.; desc. 30 ft. over SW. slope.
- 18.65 The NE 1/16 sec. cor. of sec. 15.
- Descend 240 ft. over SW. slope.
- 37.33 The center N 1/16 sec. cor. of sec. 15.

From the W 1/16 sec. cor. of secs. 15 and 22.

N. $0^{\circ} 35'$ W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 15.

Ascend 295 ft. over S. slope, through open pasture land.

- 15.80 Leave pasture, enter heavy timber and dense undergrowth, edge bears generally E. and W.
- 17.50 Ridge, bears N. 80° W. and E.; desc. 15 ft. over NE. slope.
- 19.15 Point for the SW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the SW $\frac{1}{4}$.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

SW 1/16 S15
1965

from which

A fir, 12 ins. diam., bears S. 15° E., $44\frac{1}{2}$ lks. dist., mkd. SW 1/16 S15 BT.