

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of Line Bet. Secs. 4 and 33, on S. Bdy.

CHAINS

of T. 31 S., R. 7 W.

39.32

The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, perpetuated and recorded by John M. Powell of the Douglas County Surveyor's Office, in 1966, monumented with an iron post, 1 in. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

	T 31 S	
$\frac{1}{4}$	S 33	R
	S 4	W
	T 32 S	
	1966	

from which the original bearing trees

A fir, 37 ins. diam., bears N. 70° W., 53 $\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on bark blaze. (Record Distance, 52 lks.)

A fir, 41 ins. diam., bears S. 70° E., 46 $\frac{1}{2}$ lks. dist., with scribe marks BT visible on bark blaze, and remarked $\frac{1}{4}$ S4 CS BT by Powell. (Record distance, 45 lks.)

and a bearing tree marked in 1963-64

A fir, 9 ins. diam., bears N. 65° E. 54 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

and a bearing tree marked by Powell

A fir, 7 ins. diam., bears N. 40° E., 29 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

From this point the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, established in 1963-64, bears S. 83° E., 0.29 chs. dist. Remove the iron post and destroy the marks on the SE. bearing tree.

S. 89° 28' W., beginning new measurement.

Ascend 345 ft. over NE. slope.

9.68 Spur, slopes N. 10° W.; desc. 570 ft. over SW. slope.

25.53 Creek, 3 lks. wide, course N. 65° W.; asc. 30 ft. over NE. slope.

29.53 Spur, slopes N.; desc. 35 ft. over NW. slope.

31.68 Draw, drains N.; asc. 135 ft. over NE. slope.

37.03 Spur, slopes N.; desc. 40 ft. over NW. slope.

38.74 The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, protruding 6 ins. above ground, with brass cap marked and witnessed as described in the official record.

General Description

The general description of this area is as described in the official record of the 1963-64 resurvey.