

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, 7th. Stan. Par. S., N. Bdy. of T. 33 S., R. 5 W.

CHAINS

## COUNTY SURVEYORS OFFICE

	T	32	S	
R	S	36	S	R
5	S	1	31	4
W	T	33	S	W
		1964		

from which the original bearing trees mkd. by Ives and Hyde in 1854

A douglas fir, 20 ins. diam., bears N. 42° E., 27 lks. dist., with a healed blaze.

An incense cedar stub, 48 ins. diam., bears S. 58° E., 39 lks. dist., mkd. T32S R4W S BT on a weathered blaze.

A Douglas fir, 20 ins. diam., bears S. 60° W., 17 lks. dist., with a healed blaze.

A Douglas fir, 18 ins. diam., bears N. 62° W., 20 lks. dist., with a healed blaze.

add new bearing trees

An incense cedar, 10 ins. diam., bears N. 28° W., 79 lks. dist., mkd. T32S R5WS36 BT.

A Douglas fir, 10 ins. diam., bears S. 53° W., 92 lks. dist., mkd. T33S R5W S1 BT.

The monument set by Nicklin and Chapman in 1897 was not recovered.

N. 89°39' W., along the N. bdy. of sec. 1, marking and blazing the true line.

Descend 25 ft. over NW. slope, along the edge of heavy timber, bearing E. and W.

2.25 Creek, 5 lks. wide, course N. 50° W.; desc. 15 ft. along N. slope.

22.00 Ridge, bears N. 60° W. and S. 60° E.; desc. 225 ft. over SW. slope.

40.05 The Ives and Hyde standard  $\frac{1}{4}$  sec. cor. of secs. land 36, determined at record distance from the remains of the original bearing trees. This corner now becomes an angle point of secs. 1 and 36 from which the original bearing trees

A ponderosa pine, 36 ins. diam., bears N. 18° W., 118 lks. dist., mkd.  $\frac{1}{4}$  S BT on exposed blaze.  
(Record bearing, N. 80° W.)

A stump hole bears S. 19 $\frac{1}{2}$ ° E., 63 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

AP
T 32 S R 5 W
S 36
S 1
T 33 S
1965