

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, 7th. Stan. Par. S., N. Bdy. of T. 33 S., R. 5 W.

CHAINS

from which

A Douglas fir, 8 ins. diam., bears N. 16° W.,  
29 lks. dist., mkd. AP T32S R5W S36 BT.

A Douglas fir, 6 ins. diam., bears S. 65° W.,  
65 lks. dist., mkd. AP T33S R5W S1 BT.

N. 89° 35' W., beginning new measurement.

Descend 10 ft. over SW. slope.

1.50

Point for the  $\frac{1}{4}$  sec. cor. of sec. 1 only, at mid-point longitudinally between the theoretical intersection of the north and east boundaries of sec. 1 and the closing corner of sections 1 and 2.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

      
 $\frac{1}{4}$  S 1  
T 33 S R 5 W  
1965

from which

A Douglas fir, 12 ins. diam., bears S. 38° E.,  
49 lks. dist., mkd.  $\frac{1}{4}$  S1 BT.

A Douglas fir, 6 ins. diam., bears S. 46° W.,  
43 lks. dist., mkd.  $\frac{1}{4}$  S1 BT.

Descent 10 ft. over SW. slope.

2.50

Spur, slopes SW.; desc. 80 ft. over W. slope.

3.75

Ravine, drains S. 30° W.; desc. 40 ft. over SW. slope.

11.75

Ravine, drains S. 25° W.; asc. 20 ft. over SE. slope.

13.80

Spur, slopes S. 30° W.; desc. 55 ft. over SW. slope.

19.40

Ravine, drains S.; asc. 35 ft. over E. slope.

20.70

Spur, slopes S.; desc. 10 ft. over SW. slope.

23.06

Point for the W  $\frac{1}{16}$  sec. cor. of sec. 1 only.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

      
S  $\frac{1}{16}$  S1  
1965

from which

A ponderosa pine, 18 ins. diam., bears S. 37° E.,  
69 lks. dist., mkd. W  $\frac{1}{16}$  S1 BT.

A Douglas fir, 8 ins. diam., bears S. 75° W.,  
54 lks. dist., mkd. W  $\frac{1}{16}$  S1 BT.

The corner is located at bottom of descent, slopes S.