

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 33 S., R. 5 W.

CHAINS

An incense cedar, 60 ins. diam., bears S. 41° E.,
70 lks. dist., with a weathered blaze, no marks
discernible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a mound of stone, 4 ft. base, to
top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S \ 1 \ | \ S \ 6 \\ R \ 5 \ W \ | \ R \ 4 \ W \\ T \ 33 \ S \\ 1965 \end{array}$$

from which

An incense cedar, 10 ins. diam., bears N. 52° E.,
72 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

A ponderosa pine, 15 ins. diam., bears S. 81° W.,
53 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Reset corner stone on W. side of iron post.

N. 2° 12' E., bet. secs. 1 and 6, marking and blazing
the true line.

Ascend 350 ft. over SW. slope, through sparse timber
and light undergrowth.

26.75 Sour ridge, bears N. 80° W. and S. 80° E.; desc. 430 ft.
over N. slope.

35.39 The cor. of Tps. 33 S., Rs. 4 and 5 W., only, on the S. bdy.
of sec. 31, T. 32 S., R. 4 W., monumented with an iron
post, 1½ ins. diam., supported in a mound of stone,
5 ft. base, 4 ft. high, with brass cap mkd.

COUNTY SURVEYORS OFFICE

$$\begin{array}{c} T \ 32 \ S \\ S \ 31 \\ \hline R \ S \ 1 \ | \ S \ 6 \ R \\ 5 \ T \ 33 \ S \ 4 \\ W \ 1964 \ W \end{array}$$

from which the original bearing trees mkd. by Sharp:

A Douglas-fir snag, 8 ins. diam., bears
N. 46° E., 24 lks. dist., mkd. T33S R4W & 5W BT
on a weathered blaze.

A Douglas-fir snag, 10 ins. diam., bears
S. 77° E., 16 lks. dist., mkd. T33S R4W S6 BT
on a weathered blaze.

A Douglas-fir, 16 ins. diam., bears S. 39° W.,
40 lks. dist., with healed blaze.

Thence S. 86° 28' W., along the S. bdy. of sec. 31,
T. 32 S., R. 4 W.

Descend slightly along a north slope, through heavy
timber.

1.22 The S. W. cor. of Tp. 32 S., R. 4 W., monumented with an
iron post, 1½ ins. diam., firmly set in the ground, and