

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented with a basalt stone, 14 x 12 x 10 ins., firmly set, 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the original bearing trees:

A fir, 38 ins. diam., bears N. 20° E., 200 lks. dist., with scribe marks $\frac{1}{4}$ visible on partly opened blaze. (Record, N. 19° E.)

A fir, stump, 24 ins. diam., bears S. 49 $\frac{1}{2}$ ° W., 411 lks. dist., with rotted blaze. (Record, S. 50° W., 416 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W
 $\frac{1}{4}$
 S 14 | S 13
 1967

from which a new bearing tree

A fir, 31 ins. diam., bears N. 54° W., 35 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Deposit the corner stone alongside the iron post.

The cor. of secs. 11, 12, 13, and 14, monumented with the original basalt stone, 20 x 8 x 6 ins., firmly set, 10 ins. in the ground, mkd. with 4 notches on S. and 1 notch on E. edge, from which the original bearing trees:

A cedar snag, 24 ins. diam., bears N. 48 $\frac{1}{2}$ ° E., 56 lks. dist., with scribe marks S3 5W 12 visible on partly opened blaze. (Record, N. 51° E., 60 lks.)

A fir, 34 ins. diam., bears S. 25° E., 78 lks. dist., with healed blaze. (Record, S. 21 $\frac{1}{2}$ ° E.)

A cedar, 31 ins. diam., bears S. 14 $\frac{1}{2}$ ° W., 72 lks. dist., with scribe marks 5W S14 visible on partly healed blaze. (Record, S. 16 $\frac{1}{2}$ ° W., 74 lks.)

A fir snag, 29 ins. diam., bears N. 17° W., 119 lks. dist., with scribe marks 33S 5W visible on partly opened blaze. (Record, N. 14 $\frac{1}{2}$ ° W., 121 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W
 S 11 | S 12
 S 14 | S 13
 1967

from which new bearing trees

A fir, 11 ins. diam., bears N. 54° E., 56 lks. dist., mkd. T33S R5WS12 BT.

A fir, 12 ins. diam., bears N. 60° W., 19 $\frac{1}{2}$ lks. dist., mkd. T33S R5W S11 BT.