

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,  
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Deposit the corner stone alongside the iron post.

The cor. of secs. 1, 2, 11 and 12, monumented with the original basalt stone, 10 x 8 x 6 ins., firmly set, 6 ins. in the ground, mkd. with 5 grooves on the S. face, from which the original bearing trees:

A fir, 26 ins. diam., bears N. 59° E., 7 lks. dist., with scribe marks S1 BT visible on opened blaze.

A madrone stool, bears S. 61° E., 29 lks. dist.

A down pine, 36 ins. diam., bears S. 29° W., 14.5 lks. dist., with scribe marks S BT visible on burned blaze.

A madrone stool, bears N. 27° W., 33 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W  
S 2 | S 1  
S 11 | S 12  
1966

from which new bearing trees

A cedar, 8 ins. diam., bears N. 64° E., 38 lks. dist., mkd. T33S R5W S1 BT.

A fir, 8 ins. diam., bears S. 35° E., 56 lks. dist., mkd. T33S R5W S12 BT.

A fir, 6 ins. diam., bears S. 26° W., 33 lks. dist., mkd. T33S R5W S11 BT.

A fir, 6 ins. diam., bears N. 64° W., 21 lks. dist., mkd. T33S R5W S2 BT.

Deposit corner stone alongside iron post.

The ¼ sec. cor. of secs. 1 and 12, monumented with the original basalt stone, 20 x 12 x 8 ins., firmly set, 12 ins. in the ground, mkd. ¼ on the N. face, from which the original bearing trees:

A fir, 16 ins. diam., bears N. 43° E., 23 lks. dist., with scribe marks BT visible on partly healed blaze. (Record, 14 lks.)

A fir, 14 ins. diam., bears S. 39° W., 14 lks. dist., mkd. ¼ S BT on opened blaze. (Record, 23 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 33 S R 5 W  
¼ S 1  
¼ S 12  
1966