

County Surveyor's Record, Douglas County, Oregon

Remonumentation of Certain Original Corner Points,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 12 ins. diam., bears N. 3° E., 19 lks.
dist., mkd. $\frac{1}{4}$ S1 BT.

A fir, 14 ins. diam., bears S. 5° W., 42 lks.
dist., mkd. $\frac{1}{4}$ S12 BT.

Deposit the corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with the
original basalt stone, 12 x 10 x 8 ins., firmly set,
8 ins. in the ground, mkd. $\frac{1}{4}$ on the W. face, alongside
of which is driven an iron pipe, 1 $\frac{1}{2}$ ins. diam., firmly
set, protruding 16 ins. from the ground, from which
the original bearing trees:

A sugar pine, 36 ins. diam., bears N. 41° W.,
39 lks. dist., with scribe marks $\frac{1}{4}$ S visible
on a partially healed blaze.

A Douglas-fir, 20 ins. diam., bears S. 39 $\frac{1}{2}$ ° E.,
91 lks. dist., with scribe marks $\frac{1}{4}$ S visible
on an opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 33 S R 5 W
 $\frac{1}{4}$
S 2 | S 1
1965

from which

A D. Fir 8" dia., bears S. 70° E., 68 lks. dist., mkd. $\frac{1}{4}$ S1
BT.

A D. Fir 6" dia., bears S. 3° W., 53 lks. dist., mkd. $\frac{1}{4}$ S2
BT

Deposit the corner stone and bury the iron pipe alongside
the iron post.

(end of notes pertaining to Doug. Co.)

BT information
added 1-13-95
per research of
microfilm (DC, D.C.S.O)