

T. 32 S., R. 6 W.

CHAINS

The history of surveys of township 32 south, range 6 west, Willamette Meridian, Oregon, in the portion of the township covered by the resurvey is as follows:

A portion of the subdivisional lines were surveyed by William H. Byars in 1881, as shown on the official plat of survey approved May 31, 1882.

The survey was made at the request of the Medford District Manager, for the administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding, or crossing, public lands were blazed. All lines not forming closures were chained twice.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and special instructions under Group No. 616, Oregon, dated June 2, 1966.

The directions of lines were determined by deflection angles from direct solar observations.

The geographic position of the corner of sections 14, 15, 22 and 23, as scaled from the Canyonville quadrangle map, as published by the Geological Survey, in 1954, is as follows:

Latitude 42° 47.0' N. Longitude 123° 23.2' W.

The mean magnetic declination is 20° E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 32 S., R. 6 W., Willamette Meridian, Oregon.

(Restoring the 1881 survey by William H. Byars)

The cor. of secs. 14, 15, 22 and 23, determined at record bearing and distance from the only remaining original bearing tree:

A live oak, 14 ins. diam., bears N. 50° W.,
23 lks. dist., with scribe mark 3 visible on
weathered blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 32 S	R 6 W
S 15	S 14
S 22	S 23
1966	

from which new bearing trees

A fir, 16 ins. diam., bears N. 9½° E., 69 lks.
dist., mkd. T32S R6W S14 BT.