

Dependent Resurvey, Subd. Linve, T. 32 S., R. 6 W.

CHAINS

A madrone, 10 ins. diam., bears S. 72° E., 57 lks.
dist., mkd. T32S R6W S23 BT.

A madrone, 8 ins. diam., bears S. 10° W., 43 lks.
dist., mkd. T32S R6W S22 BT.

A live oak, 12 ins. diam., bears N. 10° W., 22 lks.
dist., mkd. T32S R6W S15 BT.

N. 0° 13' W., bet. secs. 14 and 15, marking and blazing
the true line.

Ascend 180 ft. over S. slope, through heavy timber and
dense undergrowth.

7.40 Spur, slopes S. 50° W., desc. 50 ft. along W. slope.

12.90 Bottom of descent, slopes W.; asc. 10 ft. over SW. slope.

19.84 Point for the S 1/16 sec. cor. of secs. 14 and 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.
in the ground, to solid rock, and in a mound of stone,
3 ft. base, to top, with brass cap mkd.

S 1/16
S 15 | S 14
1966

FD. OK 12/19/90
T. MATH
CS 43/127

from which

A fir, 14 ins. diam., bears S. 45° E., 75 lks.
dist., mkd. S 1/16 S14 BT.

A fir, 24 ins. diam., bears N. 78° W., 23 lks.
dist., mkd. S 1/16 S15 BT.

Ascend 5 ft. over SW. slope.

21.35 Ridge, bears N. 35° W. and S. 35° E.; desc. 145 ft. over
N. E. slope.

32.10 Ravine, drains S. 65° E., asc. 70 ft. over S. E. slope.

35.15 Spur, slopes S. 80° E.; desc. 45 ft. over N. E. slope.

39.68 Point for the ¼ sec. cor. of secs. 14 and 15, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 32 S R 6 W
¼
S 15 | S 14
1966

from which

A fir, 14 ins. diam., bears S. 55° E., 70 lks.
dist., mkd. ¼ S14 BT.

A cedar, 16 ins. diam., bears N. 74° W., 26 lks.
dist., mkd. ¼ S15 BT.

Corner falls on S. bank of a creek, 2 lks. wide, course E.