

13985 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS

Descend 60 Ft. over NE. slope.

44.00 Ravine, drains E.; asc. 120 ft. over SE. slope.

49.80 Spur, slopes S. 75° E.; desc. 20 ft. over NE. slope.

52.30 Ravine, drains S. 80° E.; asc. 130 ft. over SE. slope.

59.60 Spur, slopes S. 60° E.; desc. 165 ft. over NE. slope.

68.00 Ravine, drains N. 80° E.; asc. 300 ft. over SE. slope.

x 79.36

The cor. of secs. 10, 11, 14 and 15, reestablished and recorded at proportionate distance by Lorne Swearingen, in 1963, monumented with a steel rod, 5/8 ins. diam., firmly set, protruding 6 ins. above ground; there is no remaining evidence of the original corner, from which bearing trees mkd. by Swearingen:

A fir, 20 ins. diam., bears N. 5° E., 64 lks. dist., with partially healed blaze.

A madrone, 16 ins. diam., bears S. 18° E., 32 lks. dist., with scribe marks S14 BT visible on open blaze.

A fir, 14 ins. diam., bears S. 39°W., 4 lks. dist., with partially healed blaze.

A sugar pine, 8 ins. diam., bears N. 19°W., 69 lks. dist., with partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S | R 6 W
 S 10 | S 11
 S 15 | S 14
 1966

from which new bearing trees

A fir, 10 ins. diam., bears N. 16° E., 61 lks. dist., mkd. T 32S R6W S11 BT.

A sugar pine, 24 ins. diam., bears S. 58° W., 39 lks. dist., mkd. T32S R6W S15 BT.

Insert steel rod inside from post.

x Cor. falls on spur, slopes E.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, yellow pine, oak, madrone, and chinquapin; undergrowth, poison oak, salal, Oregon grape, hazel and manzanita.

From the ¼ sec. cor. of secs. 11 and 14, monumented with an iron pipe, 1 in. diam., firmly set, protruding 12 ins. above the ground, from which the original bearing trees:

The stump hole of a down fir, 28 ins. diam., bears N. 30° E., 36 lks. dist., no marks visible on the fir.