

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS	
	<p>A fir snag, 34 ins. diam., bears S. 30° W., 4 lks, dist., no marks visible on a burned blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 6 W ¼ S 11 S 14 1966</p> <p>from which new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 5° W., 29 lks. dist., mkd. ¼ S11 BT.</p> <p>A fir, 14 ins. diam., bears S. 54° W., 25 lks. dist., mkd. ¼ S14 BT.</p> <p>Insert iron pipe inside iron post.</p> <p>Cor. falls 125 lks. W. of Lawson Creek, 12 lks. wide, course South.</p> <p>S. 87° W., bet secs. 11 and 14.</p> <p>Ascend 710 Ft. over E. slope, changing to SE. slope, through heavy timber and dense undergrowth.</p>
8.70	Abandoned railroad grade, bears N. and S.
40.67	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, chinquapin, and madrone; undergrowth, poison oak, vine maple, hazel, blackberry, salal, and Oregon grape.</p>
	<p>N. 2° 35' E., bet. secs. 10 and 11.</p> <p>Descend 100 Ft. over N. slope, through scattering timber and dense undergrowth.</p>
3.45	Ravine, drains N. 70° E.; asc. 50 ft. over SE. slope.
6.90	Spur, slopes NE.; desc. 150 ft. over NE. slope.
17.70	Ravine, drains E.; asc. 70 ft. over SE. slope.
24.70	Top of ascent, slopes E.; desc. 10 ft. along E. slope.
29.10	Creek, 3 lks. wide, course SE.: asc. 315 ft. over S. slope.
39.77	<p>The ¼ sec. cor. of secs. 10 and 11, perpetuated and recorded by J. W. Byron, Deputy Douglas County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, protruding 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE 1959 ¼ S 10 S 11 T 32 S R 6 W</p>