

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS

The stump hole of a down fir, 30 ins. diam., bears N. 18° W., 45 lks. dist., no marks visible on burned blaze on fir.

A yew stump, 12 ins. diam., bears South, 23 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 6 W
¼ S 15
S 22
1966

From which new bearing trees

A fir, 7 ins. diam., bears N. 1° E., 67 lks. dist., mkd. ¼ S15 BT.

A fir, 8 ins. diam., bears S. 55° W., 27 lks. dist., mkd. ¼ S22 BT.

Reset yew post alongside iron post.

S. 89° 30' W., beginning new measurement.

Ascend 605 Ft. over SE. slope.

19.65 Point for the W 1/16 sec. cor. of secs. 15 and 22.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 S 15
S 22
1966

From which

A fir, 12 ins. diam., bears N. 11° E., 45 lks. dist., mkd. W 1/16 S15 BT.

A fir, 7 ins. diam., bears S. 53° E., 19 lks. dist., mkd. W 1/16 S22 BT.

Ascend 615 Ft. over SE. slope.

39.30 The cor. of secs. 15, 16, 22 and 23, determined at record bearing and distance from the remains of the original bearing trees:

The stump hole of a down cedar, 40 ins. diam., bears N. 89° E., 6 lks, dist., no marks visible on the tree.

The stump hole of a down cedar, 30 ins. diam., bears S. 55° E., 38 lks. dist., no marks visible on the tree.

A madrone clump, bears S. 43° W., 20 lks. dist., (Record, laurel, S. 42° W.)

The stump hole of a down chinquapin, 16 ins. diam., bears N. 5° W., 60 lks. dist., with illegible negative scribe marks visible on overgrowth of the tree.