

13989 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 6 W
S 16 | S 15
S 21 | S 22
1966

from which new bearing trees

A fir, 12 ins. diam., bears N. 3° E., 69 lks. dist., mkd. T32S R6W S15 BT.

A chinquapin, 10 ins. diam., bears S. 70°E., 99 lks. dist., mkd. T32S R6W S22 BT.

A fir, 15 ins. diam., bears S. 60° W., 99 lks. dist., mkd. T 32S R6W S21 BT.

A chinquapin, 10 ins. diam., bears N. 61°W., 61 lks. dist., mkd. T32S R6W S16 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, yew, alder, chinquapin, and madrone; undergrowth, poison oak, vine maple, hazel, arrowwood, salal, and Oregon grape.

N. 0° 33' W., bet. secs. 15 and 16.

Ascend 10 ft. over SE. slope, through scattering timber and dense undergrowth.

- 1.25 Spur, slopes E.; desc. 250 ft. over broken NE. slope.
- 13.00 Ravine, drains N. 60° E.; asc. 15 ft. over SE. slope.
- 15.00 Spur, slopes NE. ; desc. 90 ft. over N. slope.
- 19.91 Point for the S 1/16 sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 16 | S 15
1966

from which

A fir, 34 ins. diam., bears S. 34°E., 18 lks. dist., mkd. S 1/16 S15 BT.

No other tree within limits.

Descend 45 ft. over N. slope.

- 21.00 Ravine, drains NE.:desc. 335 ft. along broken E. slope.
- 37.10 Creek, 3 lks. wide, course N. 80° E.; asc. 10 ft. over SE. slope.