

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS

39.82

Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 6 W
 $\frac{1}{4}$
 S 16/S 15
 1966

from which

A fir, 5 ins. diam., bears N. 60° E., 19 lks.
 dist., mkd. X BT.

A cedar, 18 ins. diam., bears S. 37° W., 22 lks.
 dist., mkd. $\frac{1}{4}$ S 16 BT.

Ascend 65 ft. over SE. slope, changing to E. slope.

46.40

Spur, slopes S. 75° E.; desc. 190 ft. over broken NE. slope, changing to NW. slope.

59.73

Point for the N 1/16 sec. cor. of secs. 15 and 16.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

N 1/16
 S 16/S 15
 1966

from which

A fir, 6 ins. diam., bears S. 12° E., 40 lks.
 dist., mkd. N 1/16 S15 BT.

A fir, 7 ins. diam., bears N. 2° W., 34 lks.
 dist., mkd. N 1/16 S16 BT.

Descend 175 ft. over NW. slope.

64.10

Creek, 5 lks. wide, course N. 25° E.; desc. 90 ft. over N. slope.

71.00

Wood Creek, 30 lks. wide, course S. 80° E.; asc. 120 ft. over SW. slope.

73.00

Gravelled road, 30 lks. wide, bears NW. and SE.

79.64

Point for the cor. of secs. 9, 10, 15 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S | R 6 W
 S 9 | S 10
 S 16 | S 15
 1966

from which