

13991 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS

A fir, 18 ins. diam., bears N.15° E., 47 lks. dist., mkd. T32S R6W S10 BT.

A yellow pine, 5 ins. diam., bears S. 54° E., 18 lks. dist., mkd. X BT.

A chinquapin, 8 ins.diam., bears S. 46° W., 31 lks. dist., mkd. T32S R6W S16 BT.

A fir, 15 ins. diam., bears N. 33° W., 43 lks. dist., mkd. T32S R6W S9 BT.

From this point the  $\frac{1}{4}$  sec. cor. of secs. 9 and 16, bears N. 88° 18' W., 39.53 chs. dist., monumented with a wood post, 3 x 3 ins. sq., firmly set, protruding 36 ins. above the ground, from which the original bearing trees:

A sawed sugar pine stump, 36 ins. diam., bears N. 8° E., 52 lks. dist., no marks visible on bottom of opened blaze. (Record, a pine)

The stump hole of a down fir, 32 ins. diam., bears S. 5° E., 26 lks. dist., with illegible scribe marks visible on a bark blaze on the fir.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 6 W  
 $\frac{1}{4}$  S 9  
 $\frac{1}{4}$  S 16  
 1966

from which new bearing trees

A fir, 15 ins. diam., bears N. 83° W., 49 lks. dist., mkd.  $\frac{1}{4}$  S9 BT.

A cedar, 14 ins. diam., bears S. 61° E., 15 lks. dist., mkd.  $\frac{1}{4}$  S16 BT.

Reset wood post alongside iron post.

Land, mountainous.  
 Soil, rocky clay.  
 Timber, fir, cedar, yellow pine, sugar pine, madrone, yew, alder, and chinquapin; undergrowth, poison oak, vine maple, hazel, arrowwood, lilac, salal, and Oregon grape.

From the cor. of secs. 10, 11, 14 and 15.

N. 89° 32' W., bet. secs. 10 and 15.

Ascend 575 ft. over SE. slope, changing to E. slope, through heavy timber and dense undergrowth.

22.15 Ridge, bears N.and S.; desc. 435 ft. over SW. slope.

41.51 The  $\frac{1}{4}$  sec. cor. of sec. 10 and 15, monumented with an iron rod, 1 in. diam., firmly set, protruding 6 ins. above the ground, from which the original bearing trees: