

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 6 W.

CHAINS

A fir snag, 44 ins. diam., bears N. 15° W.,  
22 lks, dist., no marks visible on a bark blaze.

A fir, 44 ins. diam., bears S. 2° E., 46 lks.  
dist., with scribe marks  $\frac{1}{4}$  BT visible on a  
bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 32 S R 6 W  
 $\frac{1}{4}$  S 10  
S 15  
1966

from which new bearing trees

A fir, 11 ins. diam., bears N. 3° E., 81 lks.  
dist., mkd.  $\frac{1}{4}$  S 10 BT.

A fir, 16 ins. diam., bears S. 88½° E., 86 lks.  
dist., mkd.  $\frac{1}{4}$  S 15 BT.

Reset iron rod alongside iron post.

S. 89° 12' W., beginning new measurement.

Descend 580 ft. over broken SW. slope.

19.98 Point for the W 1/16 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

W 1/16 S 10  
S 15  
1966

from which

A fir, 10 ins. diam., bears N. 6° E., 28 lks.  
dist., mkd. W 1/16 S 10 BT.

A fir, 6 ins. diam., bears S. 19° W., 35 lks.  
dist., mkd. W 1/16 S 15 BT.

Descend 35 ft. over SW. slope.

21.00 Creek, 2 lks. wide, course S. 10° W.; asc. 55 ft. over  
SE. slope.

24.80 Spur, slopes S.; desc. 160 ft. over SW. slope.

39.96 The cor. of secs. 9, 10, 15 and 16.

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, cedar, yellow pine, alder, chinquapin, and  
madrone; undergrowth, poison oak, vine maple, hazel,  
lilac, salal, and Oregon grape.

N. 1° 53' E., bet. secs. 9 and 10.

Ascend 15 ft. over SW. slope, through scattering timber  
and dense undergrowth.