

13997 County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 15, T. 32 S., R. 6 W.

CHAINS

41.72

The center S 1/16 sec. cor. of sec. 15.

From the center W 1/16 sec. cor. of sec. 15.

N. 0° 18' W., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 15.

Descend 40 ft. along E. slope, through scattering timber and dense undergrowth.

6.40

Wood Creek, 20 lks. wide, course S. 35° E.; asc. 120 ft. over SW. slope.

11.50

Gravelled road, 30 lks. wide, bears N. 35° W. and S. 35° E.

19.98

Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NW $\frac{1}{4}$.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

NW 1/16 S 15
1966

from which

A white fir, 18 ins. diam., bears N. 3° W.,
73 lks. dist., mkd. NW 1/16 S15 BT.

A fir, 6 ins. diam., bears S. 37° W., 17 lks.
dist., mkd. NW 1/16 S15 BT.

No tree within limits to the E.

Ascend 50 ft. over SW. slope.

21.80

Spur, slopes W.; desc. 30 ft. over NW. Slope.

26.20

Creek, 2 lks. wide, course S. 80° W.; asc. 205 ft. over SW. slope.

39.99

The W 1/16 sec. cor. of secs. 10 and 15.

From the center N 1/16 sec. cor. of sec. 15.

S. 89° 26' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 15.

Descend 510 ft. over SW. Slope through heavy timber and dense undergrowth.

19.92

The NW 1/16 sec. cor. of sec. 15.

Descend 75 ft. over SW. slope.

24.30

Gravelled road, 30 lks. wide, bears N. 30° W. and S. 30° E.

24.70

Wood Creek, 20 lks. wide, course S. 30° E.; asc. 315 ft. over E. slope.

37.00

Spur ridge, bears N. 20° E. and S. 20° W.; desc. 20 ft. over NW. slope.

39.82

The N 1/16 sec. cor. of secs. 15 and 16.