

Dependent Resurvey, Portion of E. Bdy., T. 29 S., R. 9 W.

CHAINS	
	<p>An oak, 18 ins. diam., bears S. 43 3/4° E., 461 lks. dist., with healed double blaze.</p> <p>An iron pipe, 1 in. diam., firmly set, extending 8 ins. above ground, and in a N. and S. fence line, bears West, 33 1/2 lks. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE WIT COR 22 FT EAST TO SEC COR R 9W S13 S18 S19 S24 R8W T29S 1958.</p> <p>Add marks BLM 1966 to brass cap.</p> <p>No new bearing trees available within limits.</p> <p>N. 0° 02' W., bet. secs. 13 and 18, marking and blazing the true line.</p> <p>Ascend 415 ft. over S. slope, changing to SE. slope, along the center of a gravelled county road, 30 lks. wide, bears N. and S.</p>
8.80	Leave county road, bears S. and N. 30° E.; enter open pasture land.
25.50	Leave pasture land; enter logged area with scattering timber and dense undergrowth, edge bears E. and W.
36.00	Spur, slopes E.; desc. 55 ft. over N. slope.
39.80	<p>The 1/4 sec. cor. of secs. 13 and 18, determined at record bearing and distance from the remains of the original bearing trees:</p> <p>The burned and rotted shell of a fir, 48 ins. diam., bears S. 30° E., 15 lks. dist., with scribe mark S visible on bark blaze.</p> <p>A down and rotted chinquapin, 18 ins. diam., bears N. 27° W., 44 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 9 W R 8 W 1/4 S 13/S 18 1966</p> <p>from which new bearing trees</p> <p>A fir, 24 ins. diam., bears N. 30° E., 14 1/2 lks. dist., mkd. 1/4 S18 BT.</p> <p>A white fir, 14 ins. diam., bears N. 68° W., 23 lks. dist., mkd. 1/4 S 13 BT.</p>
	<p>N. 0° 30' E., beginning new measurement.</p> <p>Descend 100 ft. over N. slope.</p>
0.03	Barbed wire fence, bears E. and W.
2.60	Ravine, drains N. 50° E.; asc. 85 ft. over SE. slope.
8.80	Spur, slopes NE. ; desc. 210 ft. over broken N. slope.