

Dependent Resurvey, Portion of E. Bdy., T. 29 S., R. 9 W.

CHAINS	
	<p>on bark blaze. (Record, 5 lks.)</p> <p>A sawed fir stump, 25 ins. diam., bears S. 67° W., 61 lks. dist., with illegible scribe marks visible on old bark blaze and with healed blaze at base. This tree has been remarked T29S R 9W S12 on bark blaze.</p> <p>and bearing trees marked by Byron</p> <p>A fir, 23 ins. diam., bears S. 30° E., 64 lks. dist., with healed double blaze.</p> <p>A fir, 18 ins. diam., bears S. 57° W., 68 lks. dist., with healed double blaze.</p> <p>A fir, 14 ins. diam., bears N. 42° W., 89½ lks. dist., with healed double blaze.</p> <p>Add marks HLM 1966 to brass cap.</p> <p>N. 0° 07' W., bet. secs. 1 and 6.</p> <p>Ascend 5 ft. over S. slope, across logged area, through scattering timber and dense undergrowth.</p>
1.30	Top of ascent, slopes NW.; desc. 195 ft. over NE. slope.
8.45	Creek, 4 lks. wide, course N. 60° E.; asc. 20 ft. over rolling land.
24.95	Lang Creek, 10 lks. wide, course S. 55° E.; asc. 50 ft. over rolling land.
40.06	<p>The ¼ sec. cor. of secs. 1 and 6, monumented with the remains of the original corner tree, a sawed fir stump, 24 ins. diam., with healed blaze on the E. and W. face, from which the remaining original bearing tree:</p> <p>A sawed fir stump, 19 ins. diam., bears N. 75° W., 21 lks. dist., with scribe marks BT visible on opened blaze.</p> <p>and bearing trees and a reference monument marked by J. W. Byron, Deputy County Surveyor, in 1958.</p> <p>A fir, 15 ins. diam., bears S. 55° E., 111 lks. dist., with healed double blaze.</p> <p>A down fir, 12 ins. diam., bears N. 54° W., 58 lks. dist., with healed double blaze.</p> <p>An iron pipe, 1 in. diam., firmly set, extending 12 ins. above the ground, bears North, 7½ lks. dist., with brass cap mkd. COUNTY SURVEYORS OFFICE WIT COR 5 FT SOUTH TO ¼ S1 R 9W S6 R&W T29S 1958</p> <p>Add marks HLM 1966 to brass cap.</p> <p>and a new bearing tree</p> <p>A white fir, 25 ins. diam., bears N. 57° W., 54 lks. dist., mkd. ¼ S1 BT.</p>
	<p>N. 0° 09' E., beginning new measurement.</p> <p>Ascend 80 ft. over gentle S. slope.</p>