

14004 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 29 S., R. 9 W.

CHAINS

- 20.00 Top of ascent, slopes E.; desc. 20 ft. over gentle N. slope.
  - 37.85 Creek, 2 lks. wide, course E.; asc. 5 ft. over rolling land.
  - 40.21 The cor. of Tps. 28 and 29 S., Rs. 8 and 9 W., monumented with an iron post, 2½ ins. diam., firmly set, extending 4 ins. above the ground, with brass cap marked and witnessed as described in the official record of the 1959 dependent resurvey.
- Land, gently rolling.  
Soil, rocky clay loam.  
Timber, fir, hemlock, cedar, oak, alder, maple, madrone, pine, and yew; undergrowth, vine maple, poison oak, salal, hazel, ocean spray, fern, blackberry, and huckleberry.

Dependent Resurvey of a Portion  
of the Subdivisional Lines, T. 29 S., R. 9 W.,  
Willamette Meridian, Oregon

(Restoring the 1855 survey by Dennis Hathorn and the  
1907 retracement by William M. Porter)

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp., perpetuated and recorded by A. Boyer, Deputy County Surveyor, in 1943, subsequently remonumented and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set in concrete, extending 20 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 29 S R 9 W  
S 35 | S 36  
S 2 | S 1  
T 30 S R 9 W  
1959

from which the remaining original bearing trees

A sawed fir stump, 36 ins. diam., bears N. 1°E., 35 lks. dist., with scribe marks BT visible on opened blaze. (Record, 32 lks.)

A rotted fir stump, 14 ins. diam., bears N. 57° W., 9 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees marked by Boyer

A rotted fir stump, 10 ins. diam., bears S. 42° W., 3 lks, dist., with scribe marks CS BT visible on opened blaze.

A maple stump, 18 ins. diam., bears N. 5°W., 52 lks. dist., with scribe marks CS S 36 T29S R9W BT visible on opened double blaze.

and a bearing tree marked by Byron

A cedar, 24 ins. diam., bears S. 66°E., 189 lks. dist., with scribe marks T30S R9W S1 CS BT visible on open double blaze.