

Dependent Resurvey, Portion of Subdivisional Lines T. 29 S., R. 9 W.

CHAINS

- 19.23 Barbed wire fence, bears E. and W.
- 20.05 Point for the N 1/16 sec. cor. of secs. 35 and 36.
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- N 1/16
S 35/S 36
1966
- from which
- A fir, 6 ins. diam., bears S. 12° E., 101 lks.
dist., mkd. N 1/16 S 36 BT.
- An oak, 6 ins. diam., bears N. 65° W., 55 lks.
dist., mkd. N 1/16 S35 BT.
- Corner is located at bottom of descent, slopes W.
- Ascend 25 ft. over SW. slope.
- 23.00 Top of ascent, slopes W.; desc. 90 ft. over NW. slope.
- 40.10 The cor. of secs. 25, 26, 35 and 36., perpetuated and recorded by J. W. Cole, Deputy County Surveyor, in 1920, monumented with an iron pipe, 2 ins. diam., firmly set, extending 3 ins. above the ground, from which the remaining original bearing trees:
- A burned oak stump, 36 ins. diam., bears
S. 27°E., 271 lks. dist., no marks remain.
- A burned oak stump, 24 ins. diam., bears S. 23°W.,
599 lks. dist., no marks remain. (Record, S.24°W.,
596 lks.)
- and bearing trees marked by J. N. Gearhart, Registered Engineer, in 1950
- A fir, 20 ins. diam., bears N. 56° E., 44 lks.
dist., with healed double blaze.
- A fir, 28 ins. diam., bears N. 68° W., 28½ lks.
dist., with healed double blaze. (now a 4-ft. stump - 6/84 Stringer)
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 29 S R 9 W
S 26 | S 25
S 35 | S 36
1966
- FD. OK 6/84
D. STRINGER
M 97-A
FD OK 11/25/94
J. ARTHUR
M 121-10
- from which a new bearing tree
- A fir, 9 ins. diam., bears S. 80½°E., 300 lks.
dist., mkd. T 29S R9W S36 BT.
- No bearing tree available to SW. within limits.
- Reset iron pipe alongside the iron post.
- Land, rolling hills.
Soil, rocky clay loam.