

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

and bearing trees marked by Byron

A cedar, 18 ins. diam., bears N. 9°E., 87½ lks. dist., with healed blaze.

A white fir, 16 ins. diam., bears S. 60° E., 41 lks. dist., with healed double blaze.

A white fir, 18 ins. diam., bears S. 73° W., 34½ lks. dist., with healed double blaze.

A white fir, 15 ins. diam., bears N. 56° W., 95 lks. dist., with healed double blaze.

Add marks HLM 1966 to brass cap.

Land, rolling hills.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, alder, maple, madrone, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, fern, ocean spray, hazel, blackberry, and huckleberry.

From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.

S. 89° 46' W., bet. secs. 13 and 24.

Across level bottom land.

0.33 Barbed wire fence, bears N. and S.; enter cultivated field, edge bears N. and S.

7.45 Reed Creek, 10 lks. wide, course SE.: asc. 5 ft. over nearly level bottom land.

14.30 Same creek, course NE.: asc. 3 ft. over nearly level bottom land.

17.85 Same creek, course SE.; leave cultivated field, enter logged area with scattering timber and dense undergrowth, edge bears NW. and SE.; asc. 70 ft. over NE. slope.

19.00 Dirt road, 10 lks. wide, bears N. 50° W. and S. 50°E.

34.00 Top of ascent, slopes N.; desc. 25 ft. over NW. slope.

40.07 The ¼ sec. cor. of secs. 13 and 24, reestablished at proportionate distance by A. Boyer, Registered Engineer, in 1955, monumented with an iron pipe, ¾ in. diam., firmly set, extending 14 ins. above the ground, from which bearing trees marked by Boyer:

A sawed fir stump, 34 ins. diam., bears N. 10½°E., 44 lks. dist., with scribe marks ¼ S13 BT visible on open blaze.

An oak, 10 ins. diam., bears S. 80½° E., 49 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 9 W
¼ S 13
¼ S 24
1966