

14012 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

- 2.70 Top of ascent, slopes W.; desc. 45 ft. over NW. slope.
- 5.30 Ravine, drains W.; asc. 30 ft. over SW. slope.
- 7.20 Top of ascent, slopes W.; desc. 220 ft. over NW. slope.
- 26.50 Creek, 4 lks wide, course N. 65° E.; asc. 10 ft. over SW. slope.
- 29.70 Top of ascent, slopes E.; desc. 20 ft. over N. slope.
- 34.00 Reed Creek, 3 lks. wide, course S. 75° E.; asc. 30 ft. over S. slope.
- 40.34 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 29 S R 9 W
 $\frac{1}{4}$
S 14/S 13
1966
- from which
- A fir, 19 ins. diam., bears N. 6° E., 60 lks. dist., mkd. $\frac{1}{4}$ S13 BT.
- A fir, 7 ins. diam., bears S. 75° W., 10 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S14 BT.
- Ascend 55 ft. over S. slope.
- 60.51 Point for the N 1/16 sec. cor. of secs. 13 and 14.
- Set an iron post. 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
- N 1/16
S 14/S13
1966
- from which
- An oak, 8 ins. diam., bears N. 65° E., 66 lks. dist., mkd. N 1/16 S13 BT.
- A white fir, 8 ins. diam., bears N. 51 $\frac{1}{2}$ ° W., 42 lks. dist., mkd. N 1/16 S14 BT.
- Ascend 15 ft. over S. slope, changing to SE. slope.
- 64.30 Top of ascent, slopes SE.; desc. 25 ft. over NE. slope.
- 67.35 Deep Creek, 2 lks. wide, course N. 80° E.; asc. 80 ft. over S. slope.
- 80.40 Dirt road, 20 lks. wide, bears NE. and SW.
- 80.68 The cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1958, monumented with an iron pipe, 1 in. diam., firmly set, extending 16 ins. above the ground, with brass cap mkd.