

14014 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS	
	<p>from which the original bearing trees</p> <p>A sawed fir stump, 24 ins. diam., bears N. 35°E., 25 lks. dist., with scribe marks BT visible on opened blaze. (Record, N. 40° E., 24 lks.)</p> <p>A sawed fir stump, 38 ins. diam., bears S. 38°W., 23 lks. dist., with scribe marks BT visible on opened blaze. (Record, 20 lks.)</p> <p>and bearing trees marked by Byron</p> <p>A fir, 10 ins. diam., bears N. 18½° W., 61 lks. dist., with healed double blaze.</p> <p>A fir, 10 ins. diam., bears S. 80½°W., 65 lks. dist., with healed double blaze.</p> <p>Add marks Blm 1966 to brass cap.</p> <hr/> <p>N. 89° 29' W., beginning new measurement.</p> <p>Ascend 105 ft. over rolling bottom land, changing to gradual SE. slope.</p>
4.10	Barbed wire fence, bears N. and S.; leave timber, enter open pasture land, edges bear N. 65°E. and S.
8.91	Barbed wire fence, bears N. and S.; leave pasture land, enter logged area with scattering timber and dense undergrowth.
10.70	Gravelled road, 20 lks. wide, bears N. and S.
12.50	Dirt road, 15 lks. wide, bears N. 55°E. and S. 55°W.
24.30	Top of ascent, slopes S.; desc. 25 ft. over gradual SW. slope.
36.30	Ravine, drains S.; asc. 30 ft. over SE. slope.
39.95	Dirt road, 20 lks. wide, bears NE. and SW.
40.17	The cor. of secs. 11, 12, 13, and 14.
	<p>Land, rolling bottom land. Soil, rocky clay loam. Timber, fir, hemlock, cedar, oak, alder, maple, madrone, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, ocean spray, fern, hazel, blackberry, and huckleberry.</p> <hr/> <p>N. 0°17' W., bet. secs. 11 and 12.</p> <p>Ascend 145 ft. over SE. slope, across logged area, through scattering timber and dense undergrowth.</p>
6.25	Dirt road, 15 lks. wide, bears N. 85° E. and S. 75°W.
16.00	Spur, slopes N. 70°E.; desc. 180 ft. over NE. Slope.
30.85	Dry creek bed, 6 lks. wide, drains S. 70°E.; asc. 165 ft. over SE. slope.
32.00	The SE. cor. of old growth timber, edges bear generally N. and W.; continue along W. edge of logged area.