

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 29\ S\ R\ 9\ W \\ \quad S\ 2\ |S\ 1 \\ \hline S\ 11\ |S\ 12 \\ \quad 1966 \end{array}$$

from which

A fir, 16 ins. diam., bears N. 70°E., 64½ lks. dist., mkd. T29S R9W S1 BT.

A fir, 11 ins. diam., bears S. 54½°E., 78 lks dist., mkd. T29S R9W S12 BT.

A fir, 10 ins. diam., bears S. 4° W., 55 lks. dist., mkd. T29S R9W S11 BT.

A fir, 15 ins. diam., bears N. 9½° W., 123 lks. dist., mkd. T29S R9W S2 BT.

Land, mountainous.

Soil, rocky clay loam.

Fir, cedar, oak, alder, maple, madrone, Timber, hemlock, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, ocean spray, fern, hazel, blackberry, and huckleberry.

From the cor. of secs. 1, 6, 7, and 12, on the E. bdy. of the Tp.

N. 89° 25' W., bet. secs. 1 and 12.

Descend 150 ft. over W. slope, changing to NW. slope, across logged area, through scattering timber and dense undergrowth.

0.02 Barbed wire fence, bears N. and S.

19.60 Dirt road, 10 lks. wide, bears N. and S.

20.06 Barbed wire fence, bears N., S. and W.; leave timber, enter open pasture land, edges bear N. 40° E. and S. 70° W.; continue generally along fence.

22.00 Bottom of descent, slopes S. 30°W.; asc. 65 ft. over rolling SE. slope.

32.00 Leave open pasture land; enter logged area with scattering timber and dense undergrowth, edge bears N. and S.

40.17 Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 29\ S\ R\ 9\ W \\ \quad \frac{1}{4}\ S\ 1 \\ \quad \quad S\ 12 \\ \quad 1966 \end{array}$$

from which