

14018 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines. T. 29 S., R. 9 W.

CHAINS	
66.80	Spur, slopes S. 70° E.; desc. 220 ft. over NE. slope.
72.60	Creek, 1 lk. wide, course S. 70½ E.; asc. 135 ft. over SE. slope.
75.50	Spur, slopes E.; desc. 50 ft. over NE. slope.
77.00	Ravine, drains E.; asc. 100 ft. over SE. slope.
79.62	<p>The cor. of secs. 1, 2, 35, and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, extending 4 ins. above the ground, with brass cap marked and witnessed as described in the official record of the 1959 dependent resurvey.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, oak, maple, alder, madrone, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, ocean spray, fern, hazel, blackberry, and huckleberry.</p>
19.86	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89° 39' W., bet. secs. 23 and 26.</p> <p>Descend 5 ft. over gradual W. slope, generally along an E. and W. fence, through open pasture land.</p> <p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E 1/16 $\frac{S}{S}$ $\frac{23}{26}$</p> <p>1966</p> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears N. 44° E., 182 lks. dist., mkd. E 1/16 S23 BT.</p> <p style="padding-left: 40px;">An apple, 8 ins. diam., bears S. 37½° W., 94 lks. dist., mkd. E 1/16 S26 BT.</p> <p>Corner is located 7 lks. North of E. and W. fence.</p> <p>Descend 15 Ft. over gradual W. slope.</p>
34.95	Holmes Creek, 1 lk. wide, course S.; asc. 30 ft. over E. slope.
39.72	<p>The ¼ sec. cor. of secs. 23 and 26, perpetuated and recorded by J. W. Cole, Deputy County Surveyor, in 1920, determined from an original bearing tree which is no longer in existence, monumented with an iron axle, 1 in. diam., firmly set, extending 8 ins. above the ground, from which the remains of bearing trees marked by Cole:</p> <p style="padding-left: 40px;">A stump hole with fir roots bears N. 81° W., 76 lks. dist.</p> <p style="padding-left: 40px;">A sawed fir stump, 58 ins. diam., bears S. 31½° W., 93 lks. dist., no marks visible.</p> <p>and bearing trees marked by J. W. Byron, Deputy County Surveyor, in 1959</p>