

Dependent Resurvey, Portion of Subdivisional Lines. T. 29 S., R. 9 W.

CHAINS

A white fir, 15 ins. diam., bears S. 67° E.,
51½ lks. dist., with healed double blaze.

A fir, 28 ins. diam., bears S. 31½° W., 42 lks.
dist., with healed double blaze.

A hemlock, 13 ins. diam., bears N. 32° W., 48½ lks.
dist., with scribe marks T29S R9W S22 CS BT
visible on open blaze.

Add marks ELM 1966 to brass cap.

The corner is located 8 lks. N. of a fence corner, fence
lines extending S. and E.

Land, rolling hills.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, oak, alder, madrone, maple,
chinquapin, and yew; undergrowth, vine maple, poison oak,
salal, ocean spray, fern, hazel, blackberry, and huckleberry.

N. 0° 12' W., bet. secs. 22 and 23.

Ascend 130 ft. over SW. slope, along E. edge of logged
area, through heavy timber and dense undergrowth.

12.00 Spur, slopes E.; desc. 130 ft. over NE. slope.

19.00 Creek, 1 lk. wide, course N. 75° E.; asc 205 ft. over
S. slope.

27.00 The NW. cor. of old growth timber, edges bear S. and E.;
continue across logged area, through scattering timber
and dense undergrowth.

28.50 Spur, slopes SE.; desc. 10 ft. along E. slope, changing to
NE. slope.

40.01 The ¼ sec. cor. of secs. 22 and 23, perpetuated and re-
corded by J. W. Byron, Deputy County Surveyor, in 1959,
monumented with an iron pipe, 1 in. diam., firmly set,
extending 12 ins. above the ground, with brass cap mkd.

*FOOK
J. W. Byron
9/96 M/25-74*

COUNTY SURVEYORS OFFICE

T 29 S R 9 W

¼ S 22/S 23

1959

from which the remaining original bearing tree

A down fir, 40 ins. diam., bears S. 50° W.,
121 lks. dist., with scribe marks ½ visible
on bark blaze.

and bearing trees marked by Byron

A cedar, 15 ins. diam., bears N. 26° E., 142 lks.
dist., with healed double blaze.

A white fir, 17 ins. diam., bears S. 28° W., 107
lks. dist., with healed double blaze.

Add marks ELM 1966 to brass cap.

N. 0° 24' W., beginning new measurement.