

Dependent Resurvey, Portion of Subdivisional Lines T. 29 S., R. 9 W.

CHAINS

Descend 95 ft. over NE. slope.

15.10 Creek, 1 lk. wide, course S. 70° E.; asc. 165 ft. over S. slope.

16.30 Dirt road, 20 lks. wide, bears N. 70° W. and S. 70°E.

24.50 Spur, slopes S. 70° E.; desc. 165 ft. over N. slope.

31.70 Creek, 1 lk. wide, course S. 70°E.; asc, 160 ft. over S. slope.

40.02 The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, extending 18 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
 T 29 S R 9 W
 S 15 | S 14
 S 22 | S 23
 1959

from which the remaining original bearing tree

A down fir, 24 ins. diam., bears S. 6° W., 9 lks. dist., with illegible scribe marks visible on partly opened blaze.

and bearing trees marked by William Porter in 1907

A rotted fir stump, 12 ins. diam., bears S. 70°E., 38 lks. dist., with scribe marks 23 BT visible on open blaze. (Record, S. 70°W.)

A fir, 23 ins. diam., bears N. 65°W., 27 lks. dist., with scribe marks S \$9W S15 BT visible on open blaze. (Record, 26 lks.)

and bearing trees marked by Byron

A fir, 16 ins. diam., bears N. 2° E., 16½ lks. dist., with scribe marks T29S R9W S14 CS BT visible on partly healed double blaze.

A cedar, 18 ins. diam., bears S. 47° E., 65 lks. dist., with scribe marks T29S R9W S23 CS BT visible on partly healed double blaze.

A fir snag, 18 ins. diam., bears S. 60°W., 40 lks. dist., with scribe marks T29S R9W S22 CS BT visible on double blaze.

and a new bearing tree

A cedar, 13 ins. diam., bears S. 19° W., 30 lks. dist., mkd. T29S R9W S22 BT.

Add marks ELM 1966 to brass cap.

Land, rolling hills.
 Soil, rocky clay loam.
 Timber, fir, hemlock, cedar, alder, maple, oak, madrone, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, ocean spray, fern, hazel, blackberry, and huckleberry.

From the cor. of secs. 13, 14, 23, and 24.