

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 9 W.

CHAINS

Add marks BLM 1966 to brass cap.

The corner is located at edge of timber, bears N. and S.

N. 89° 42'W., beginning new measurement.

Descend 60 ft. over SW. slope, across logged area, through scattering timber and dense undergrowth.

13.05 Holmes Creek, 2 lks. wide, course S. 50°E.; asc. 160 ft. over NE. slope.

23.50 Spur, slopes S. 70°E.; asc. 105 ft. over SE. slope.

31.80 Top of ascent, slopes S.; desc. 10 ft. along broken S. slope.

39.99 The cor. of secs. 14, 15, 22, and 23.

Land, rolling hills.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, alder, maple, oak, madrone, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, ocean spray, fern, hazel, blackberry, and huckleberry.

From the cor. of secs. 10, 11, 14, and 15, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, extending 16 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 29 S R 9 W
S 10 | S 11
S 15 | S 14
1959

from which the remaining original bearing tree

The rotted remains of a fir stump, size indeterminate, bears S. 60° W., 176 lks. dist.

and bearing trees marked by William Porter, in 1907

A fir, 40 ins. diam., bears N. 5° E., 52 lks. dist., with illegible scribe marks visible on partly opened blaze. (Record, 54 lks.)

A fir, 33 ins. diam., bears S. 45° E., 34 lks. dist., with scribe marks 14 visible on partly opened blaze.

and bearing trees marked by Byron

A fir, 17 ins. diam., bears N. 52°E., 19 lks. dist., with healed double blaze.

A fir, 11 ins. diam., bears S. 29°W., 5½ lks. dist., with healed double blaze.

A fir, 8 ins. diam., bears N. 55°W., 22 lks. dist., with healed double blaze.

Add marks BLM 1966 to brass cap.

N. 0° 30' E., bet. secs. 10 and 11.