

Dependent Resurvey, Portion of Subdivisional Lines T. 29 S., R. 9 W.

CHAINS	
5.55	<p>Descend 45 ft. over NE. slope, along the E. edge of logged area, through heavy timber and dense undergrowth.</p> <p>Creek, 1 lk. wide, course S. 60°E.; asc. 405 ft. over SE. slope.</p>
24.30	<p>Spur, slopes E.; desc. 420 ft. over NE. slope.</p>
32.80	<p>Creek, 1 lk. wide, course N. 75°E.; asc. 95 ft. over SE. slope.</p>
40.16	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p>T 29 S R 9 W $\frac{1}{4}$ S 10 S 11 1966</p>
	<p>from which</p>
	<p>A hemlock, 13 ins. diam., bears N. 83° E., 31 lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p>
	<p>A fir, 15 ins. diam., bears N. 39°W., 18 lks. dist., mkd. $\frac{1}{4}$ S10 BT.</p>
	<p>Ascend 220 ft. over SE. slope.</p>
45.50	<p>Spur, slopes E.; desc. 470 ft. over NE. slope.</p>
54.45	<p>Creek, 1 lk. wide, course N. 40°E.; desc. 210 ft. over NE. slope.</p>
62.90	<p>Creek, 1 lk. wide, course NE.: asc. 55 ft. over SE. slope.</p>
64.50	<p>Spur, slopes E.; desc. 50 ft. over NE. slope.</p>
66.10	<p>Creek, 1 lk. wide, course S. 65°E.; asc. 480 ft. over SE. slope.</p>
79.70	<p>Spur, slopes E.; desc. 10 ft. along E. slope.</p>
80.32	<p>The cor. of secs. 2, 3, 10, and 11, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, extending 18 ins. above the ground, with brass cap mkd.</p>
	<p>COUNTY SURVEYORS OFFICE T 29 S R 9 W S 3 S 2 S 10 S 11 1959</p>
	<p>from which the original bearing trees</p>
	<p>A fir, 28 ins. diam., bears N. 45° E., 59 lks. dist., with large rock resting against blaze. This tree has been remarked T29S R9W S2 CS on bark blaze, by Byron.</p>
	<p>A fir, 28 ins. diam., bears S. 60°E., 29 lks. dist., with scribe marks T29S R9W S11 visible</p>