

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines. T. 29 S., R. 9 W.

CHAINS

on weathered bark blaze and with healed blaze at base. This tree has been remarked T29S R9W S11 BT on bark blaze. (Record, S. 65° E.)

A down fir, 48 ins. diam., bears S. 85° W., 36 lks. dist., no marks visible.

A down and rotted fir, 36 ins. diam., bears N. 55° W., 75 lks. dist., no marks visible.

and bearing trees marked by Byron

A hemlock, 9 ins. diam., bears S. 1° W., 34 lks. dist., with scribe marks S10 CS visible on partly healed double blaze.

A hemlock, 8 ins. diam., bears N. 50° W., 8½ lks. dist., with scribe marks S3 CS BT visible on partly healed double blaze.

Add marks BLM 1966 to brass cap.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, maple, oak, alder, madrone, chinquapin, and yew; undergrowth, vine maple, poison oak, salal, ocean spray, fern, hazel, blackberry, and huckleberry.

From the cor. of secs. 1, 2, 11, and 12.

S. 89° 59' W., bet. secs. 2 and 11.

Descend 40 ft. over SW. slope, across logged area, through scattering timber and dense undergrowth.

1.10 Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.

9.30 Wildcat Creek, 10 lks. wide, course S. 40° E.; asc. 230 ft. over NE. slope.

27.40 Top of ascent, slopes NE.: desc. 15 ft. over NW. SLOPE.

30.00 Ravine, drains NE.; asc. 370 ft. over NE. slope.

37.20 Spur, slopes NE.; desc. 5 ft. over NW. slope.

39.92 The ¼ sec. cor. of secs. 2 and 11, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, extending 12 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S R 9 W

¼ S 2
S 11

1959

from which the original bearing trees

A sawed fir stump, 38 ins. diam., bears N. 58° W., 86 lks. dist., with scribe marks ¼ S2 visible on weathered bark blaze and BT visible on opened blaze at the base. This tree has been remarked ¼ S2 on bark blaze. (Record, N. 55° W., 51 lks.)