

Remonumentation of Certain Original Corner Points,

T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which the remaining original bearing tree

A fir, 42 ins. diam., bears N. 67° E., 16 lks. dist., with scribe marks $\frac{1}{4}$ S visible on weathered bark blaze and with healed blaze at base.

and bearing trees marked by Byron

A white fir, 12 ins. diam., bears N. 31° E., 25 $\frac{1}{2}$ lks. dist., with healed double blaze.

A fir, 17 ins. diam., bears S. 13° W., 57 lks. dist., with healed double blaze.

Add marks BLM 1966 to brass cap.

The cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron pipe, 1 in. diam., firmly set, extending 14 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S R 9 W
 S 34 | S 35
 S 3 | S 2
 T 30 S R 9 W
 1959

from which the remaining original bearing trees

A cedar, 15 ins. diam., bears S. 50° E., 34 $\frac{1}{2}$ lks. dist., with scribe marks T30S R9W S2 BT visible on open blaze. (Record, S. 54° E., 51 lks.)

A white fir, 32 ins. diam., bears S. 51° W., 7 lks. dist., with illegible scribe marks visible on opened blaze.

and bearing trees marked by Byron

A white fir, 17 ins. diam., bears N. 9° E., 38 lks. dist., with healed double blaze.

A cedar, 13 ins. diam., bears N. 40° W., 44 lks. dist. with scribe marks T29S R9W S34 CS BT visible on partly healed blaze.

Add marks BLM 1966 to brass cap.

Subdivisions, T. 29 S., R. 9 W.,
 Willamette Meridian, Oregon

(Remonumenting corners established by Dennis Hathorn, in 1855)

The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1957, determined from the original bearing trees of which only 1 remains, monumented with an iron pipe, 1 in. diam., firmly set, extending 14 ins. above the ground, with brass cap mkd.