

Remonumentation of Certain Original Corner Points,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

and rehabilitated by J. W. Byron, Deputy County Surveyor, in 1957, now determined at record distance from bearing trees marked by Cowder:

An oak, 23 ins. diam., bears N. 57°W., 186½ lks. dist., with healed double blaze.

A white fir stump, 12 ins. diam., bears N. 7½°W., 118 lks. dist., with scribe marks ¼ S26 T29S R9W BT visible on unhealed double blaze.

and a bearing tree marked by Byron

An oak, 13 ins. diam., bears N. 63°E., 27 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., the top 6 ins. below the surface of a gravelled driveway, 15 lks. wide, bears N. and S., with brass cap mkd.

T 29 S R 9 W
¼ S 26
S 35
1966

from which anew bearing tree

A fir, 8 ins. diam., bears S. 41 ¾° W., 441 lks. dist., mkd. ¼ S35 BT.

The ¼ sec. cor. of secs. 11 and 14, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1957, monumented with an iron pipe, 1 in. diam., firmly set, extending 16 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 29 S R 9 W
S 11 ¼
S 14
1957

from which the original bearing trees

A fir, 42 ins. diam., bears North, 64 lks. dist., with scribe marks ¼ S visible on bark blaze and with healed blaze at base.

A fir, 27 ins. diam., bears S. 17°W., 40 lks. dist., with healed blaze. (Record, S. 21°W.)

and bearing trees marked by Byron

A hemlock, 8 ins. diam., bears N. 49°W., 4½ lks. dist., with scribe marks ¼ S11 CS BT visible on unhealed double blaze.

A fir, 15 ins. diam., bears South, 53 lks. dist., with healed double blaze.

Add marks ELM 1966 to brass cap.

GENERAL DESCRIPTION

The lands included in the foregoing survey are