

Dependent Resurvey, Portion of S. Bdy., T. 29 S., R. 3 W.

CHAINS

N. 89° 32' W., on the S. bdy. of sec. 33.

Descend 205 ft. over W. slope, through heavy timber and dense undergrowth.

6.785

The closing cor. of secs. 3 and 4, on the N. bdy. of T. 30 S., R. 3 W., monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the field notes of the 1967 dependent resurvey of the line bet. secs. 3 and 4, T. 30 S., R. 3 W.

Descend 475 ft. over W. slope.

26.255

Point for the E 1/16 sec. cor. of sec. 4 only, on the N. bdy. of T. 30 S., R. 3 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

E 1/16 S 4
1967

from which

A fir, 25 ins. diam., bears S. 42° E., 73 lks.
dist., mkd. E 1/16 S4 BT.

A fir, 6 ins. diam., bears S. 67½° W., 25½ lks.
dist., mkd. E 1/16 S4 BT.

Descend 120 ft. over W. slope.

31.00

Dry bed of creek, 4 lks. wide, course NW.; asc. 5 ft. over NE. slope.

33.20

Top of ascent, slopes N.; desc. 35 ft. over NW. slope.

35.75

Dry bed of creek, 2 lks. wide, course N. 30° W.; continue along N. slope.

39.555

Point for the ¼ sec. cor. of sec. 33 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
¼ S 33
1967

from which

A fir, 16 ins. diam., bears N. 9½° E., 151 lks.
dist., mkd. ¼ S33 BT.

A fir, 6 ins. diam., bears N. 33½° W., 111 lks.
dist., mkd. ¼ S33 BT.

Ascend 160 ft. over NE. slope.

45.725

Point for the ¼ sec. cor. of sec. 4 only, on the N. bdy. of T. 30 S., R. 3 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.