

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 3 W.

8	CHAINS	
		Ascend 10 ft. along W. slope, through heavy young timber and dense undergrowth.
	4.00	Spur, slopes NW.: desc. 580 ft. over N. slope.
	20.50	Creek, 2 lks. wide, course NW.: asc. 35 ft. over broken SW. slope.
	28.75	Top of ascent, slopes W.; desc. 110 ft. over NW. slope.
	36.40	Bottom of descent, drains W.; asc. 65 ft. over SW. slope.
	38.50	Abandoned dirt road, 15 lks. wide, bears N. 60°W. and S. 60° E.
	40.38	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 in. diam., firmly set, extending 6 ins. above ground, with brass cap mkd.
		COUNTY SURVEYORS OFFICE $\frac{1}{4}$ S   S 33   34 T 29 S R 3 W 1959
		from which the remaining original bearing tree
		A fir, 27 ins. diam., bears S. 68°W., 11 lks. Dist., with original bark scribes $\frac{1}{4}$ S BT visible. Remarkd by Byron in 1959, blaze now healed.
		and a new bearing tree
		A fir, 13 ins. diam., bears N. 69 $\frac{3}{4}$ °E., 62 lks. dist., mkd. $\frac{1}{4}$ S34 BT.
		<hr style="width: 20%; margin: 0 auto;"/>
		N. 2° 45' E., beginning new measurement.
		Ascend 20 ft. over SW. slope.
	1.00	Top of ascent, slopes W.; desc. 120 ft. over NW. slope.
	4.05	Dry bed of creek, 2 lks. wide, course N. 55°W.; asc. 145 ft. over SW. slope.
	11.50	Top of ascent, slopes SW.: desc. 45 ft. over NW. slope.
	17.80	Bottom of descent, drains S. 80° W.; asc. 10 ft. over SW. slope.
	19.70	Spur, slopes N. 50° W.; desc. 15 ft. over N. slope.
	20.49	Point for the N $\frac{1}{16}$ sec. cor. of secs. 33 and 34.
		Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
		N $\frac{1}{16}$ S 33   S 34 1967
		from which
		A fir, 50 ins. diam., bears N. 72°E., 10 lks. dist., mkd. N $\frac{1}{16}$ S34 BT.