

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines. T. 29 S., R. 3 W.

CHAINS

A fir, 33 ins. diam., bears N.  $63\frac{1}{2}^{\circ}$ W., 44 lks. dist., mkd. N 1/16 S33 BT.

Descend 435 ft. over NE. slope.

30.29

From this point a witness point established by Hathorn in 1857, but not recovered by Byars in 1881, bears East, 0.72 chs. dist., monumented with the original corner tree, a sawed fir stump, 38 ins. diam., with a healed blaze on E. and with scribe marks S33 visible on partially opened blaze on W. side, from which the remaining original bearing tree:

A sawed fir stump, 26 ins. diam., bears N.  $85^{\circ}$ W., 18 lks. dist., with a healed blaze.

35.00

Abandoned gravelled road, 20 lks. wide, bears N.  $60^{\circ}$  W. and S.  $50^{\circ}$ E.

36.25

Abandoned dirt road, 15 lks. wide, bears N.  $60^{\circ}$ W. and S.  $50^{\circ}$  E.

37.00

Creek, 3 lks. wide, course W.; asc. 10 ft. over SW. slope.

39.60

Abandoned dirt road, 15 lks. wide, bears N.  $50^{\circ}$ W. and S.  $65^{\circ}$ E.

40.98

The cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by B. B. Irving, Deputy County Surveyor, in 1941, again perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 in. diam., firmly set, extending 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S 28 | S 27  
 S 33 | S 34  
 T 29 S R 3 W  
 1959

from which the remaining original bearing trees

A fir, 33 ins. diam., bears N.  $63^{\circ}$  E.,  $75\frac{1}{2}$  lks. dist., with the original healed blaze and bark scribed T 29S R 3W 27 CS BT by Irving in 1941. (Record, N.  $62^{\circ}$  E., 73 lks.)

A fir, 27 ins. diam., bears S.  $87\frac{1}{2}^{\circ}$ W., 50 lks. dist., with scribe marks 33 visible on partially opened original blaze and bark scribed T29S R3W S33 CS by Irving in 1941. (Record, S.  $89^{\circ}$ W., 53 lks.)

A sawed fir stump, 30 ins. diam., bears N.  $89\frac{1}{2}^{\circ}$ W., 54 lks. dist., with scribe marks BT visible on the remaining portion of opened blaze. (Record, N.  $89^{\circ}$ W., 51 lks.)

and a bearing tree mkd. by Irving in 1941

The root hole of an uprooted fir, 23 ins. diam., bears S.  $16^{\circ}$ E., 14 lks. dist., with CS and other illegible bark scribes visible.

and bearing trees mkd. by Byron in 1959

A fir, 15 ins. diam., bears N.  $24\frac{1}{2}^{\circ}$ E., 27 lks. dist., with a healed double blaze.