

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 3 W.

CHAINS

the ground, with brass cap mkd.

T 29 S R 3 W
 $\frac{1}{4}$ S 28
 S 33
 1967

S. 89° 1' W., beginning new measurement.

Descend 10 ft. over SW. slope.

1.40 Bottom of descent, drains S.; asc. 40 ft. over SE. slope, changing to E. slope.

5.86 Power and telephone line, bears NW. and SE.

6.95 Gravelled road, 25 lks. wide, bears N. 65°W. and SE.

8.00 Saddle in spur ridge, bears N. and S.; desc. 65 ft. over W. slope.

16.77 May creek, 3 lks. wide, course S.; asc. 375 ft. over E. slope.

40.48 The cor. of secs. 28, 29, 32, and 33.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, madrone, oak, maple, alder, pine, and willow; undergrowth, young timber, fern, salal, poison oak, huckleberry, hazel, vine maple, Oregon grape, and blackberry.

From the cor. of secs. 9, 10, 15 and 16.

N. 89° 51' W., bet. secs. 9 and 16.

Descend 290 ft. over SW. slope, along the N. edge of logged area, through heavy timber and dense undergrowth.

22.30 Ravine, drains SW., curving W.; desc. 50 ft. over SW. slope.

25.25 Creek, 2 lks. wide, course SW.; desc. 115 ft. over SW. slope.

31.45 Gravelled road, 20 lks. wide, bears N. and S.

38.05 Weaver Creek, 15 lks. wide, course S.; asc. 5 ft. over E. slope.

40.39 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
 $\frac{1}{4}$ S 9
 S 16
 1966

from which

A cedar, 7 ins. diam., bears N. 25°E., 15 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S9 BT.