

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 3 W.

CHAINS

A fir, 6 ins. diam., bears S. 4° E., 39 lks.
dist., mkd. $\frac{1}{4}$ S16 BT.

Ascend 160 ft. over general E. slope.

47.50 Ravine, drains S. 70°E.; asc. 200 ft. over E. slope.

55.50 Spur, slopes S. 50° E.; asc. 80 ft. over SE. slope.

63.50 Spur, slopes S. 30°E.; desc. 50 ft. over SW. slope.

67.70 Ravine, drains SE.; asc. 190 ft. over E. slope.

78.70 Dirt road, 10 lks. wide, bears N. and S.

79.00 Ridge, bears N. 20° W. and S. 20°E.; desc. 15 ft. over SW. slope.

80.60 The cor. of secs. 8, 9, 16 and 17, perpetuated with a 4 ins. square madrone stake, firmly set, extending 48 ins. above ground, from which the remaining original bearing trees:

A madrone stump, 33 ins. diam., bears
N. 55° E., 13 lks. dist., with opened blaze.
no marks remaining.

A madrone root-crown, bears N. 60° W., 85 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 29 S	R 3 W
S 8 S 9	
S 17 S 16	
1966	

from which new bearing trees

A fir, 12 ins. diam., bears N. 77° E., 99 lks.
dist., mkd. T29S R3W S9 BT.

A madrone, 18 ins. diam., bears S. 55°E., 111 lks.
dist., mkd. T29S R3W S16 BT.

A madrone, 4 ins. diam., bears S. 33°W., 53 lks.
dist., mkd. X BT.

A cedar, 30 ins. diam., bears N. 4°W., 51 lks.
dist., mkd. T29S R3W S8 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, oak, pine, chinquapin, maple, dogwood, yew, and alder; undergrowth, vine maple, poison oak, salal, fern, hazel, ocean spray, Oregon grape, huckleberry, blackberry, rhododendron, and manzanita.

N. 0° 17'E., bet. secs. 8 and 9.

Ascend 15 ft. over SW. slope, along E. edge of logged area, through scattering timber and dense undergrowth.

4.90 Dirt road, 10 lks. wide, bears N. 20°W. and S. 20°E.,