

Dependent Resurvey, Portion of Subdivisional Lines, T. 29 S., R. 3 W.

CHAINS

7.00 Bottom of descent, slopes E.; asc. 155 ft. over SE. slope.

18.70 Top of ascent, slopes E.; desc. 75 ft. over NE. slope.

27.00 Ravine, drains E.; asc. 190 ft. over SE. slope.

38.85 The cor. of secs. 4, 5, 8 and 9, perpetuated and recorded by Warren D. Hootman, Registered Land Surveyor, in 1961, monumented with an iron pipe, 2 ins. diam., firmly set, extending 3 ins. above ground, from which the remaining original bearing trees:

The burned remains of a cedar snag, original size indeterminate, now 28 ins. diam., bears S. 80°E., 18 lks. dist., no marks remaining. (Record, 14 lks.)

A madrone, 12 ins. diam., bears S. 66° W., 17½ lks. dist., remarked by Hootman S8BT. (Record, 16 lks.)

The shell of a madrone, 24 ins. diam., bears N. 35° W., 42 lks. dist., no marks remaining. (Record, N. 40°W.)

and bearing trees marked by Hootman

A madrone, 13 ins. diam., bears N. 66°E., 76½ lks. dist., with scribe marks S4 BT visible on open blaze.

A madrone, 17 ins. diam., bears S. 45°E., 14 lks. dist., with scribe marks S9 BT visible on open blaze.

A fir, 21 ins. diam., bears N. 35°W., 17½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
 S 5 | S 4
 S 8 | S 9
 1966

Deposit the iron pipe alongside the iron post.

The corner is located on a spur, slopes E.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, oak, pine, chinquapin, maple, dogwood, yew, and alder; undergrowth, vine maple, poison oak, salal, fern, hazel, ocean spray, Oregon grape, huckleberry, blackberry, rhododendron, and manzanita.

From the cor. of secs. 3, 4, 9 and 10.

N. 89° 12'W., bet. secs. 4 and 9.

Ascend 235 ft. over E. slope, across logged area, through scattering timber and dense undergrowth.

9.00

Ridge, bears N. and S.; desc. 420 ft. over NW. slope.